-P.202<規格表>

P寸法の注釈を追加

| Catalog No. | | В | | | М | | | | | | | | M 1 | | | ¥単価 1~9コ | | | | | |
|--|----|------|----|----|------|-----|------|-----|------|----|----------------|----|------|----|-------------|----------|--------|--------|----------------|------------------|------------------|
| Туре | D | 選択 | D1 | Н | (並目) | d | R | W | X | Υ | Z | h | (並目) | Y1 | P | SCSNK | PSCSNK | SSCSNK | SCKNK SCJNK | PSCKNK PSCJNK | SSCKNK SSCJNK |
| (スタンダードタイプ) SCSNK PSCSNK | 6 | 8 | 20 | 17 | M3 | 3.4 | 3 | - | 6 | 4 | 6~6.5 7~9 | _ | | | | 560 | 640 | 980 | _ | _ | _ |
| | | 10 | 20 | 17 | M4 | 4.5 | 3.75 | 1 | | | | | | | | 560 | 640 | 980 | _ | _ | _ |
| | 8 | 8 | 25 | 19 | M3 | 3.4 | 3 | | 8 | | | | | | | 610 | 700 | 1,020 | - | _ | _ |
| | | 10 | 20 | 15 | M4 | 4.5 | 3.75 | | 0 | | | | | | | 610 | 700 | 1,020 | _ | _ | _ |
| | 10 | 8 | | | M3 | 3.4 | 3 | | 9 | 5 | 8~10 | | | | | 640 | 740 | 1,030 | _ | _ | _ |
| SSCSNK | 10 | * 10 | 30 | 22 | M4 | 4.5 | 3.75 | | | J | 9~10 | 7 | M4 | 10 | © 10 | 640 | 740 | 1,030 | 840 | 940 | 1,230 |
| SSCSINK | 12 | * 10 | | 22 | | | | | 10 | | | ' | IVIT | 10 | 10 | 640 | 740 | 1,030 | 870 | 940 | 1,230 |
| (カット面取付穴タイプ) | 12 | 12 | | | M5 | 5.5 | 4.5 | | | | | _ | _ | _ | _ | 670 | 740 | 1,100 | _ | _ | _ |
| | 15 | * 10 | 34 | 34 | M4 | 4.5 | 3.75 | | 11.5 | | 10~11 | 7 | M4 | 12 | 12 | 730 | 850 | 1,130 | 930 | 1,050 | 1,330 |
| SCKNK | 16 | 12 | 35 | 24 | | 5.5 | 4.5 | 1.5 | 12 | 6 | 11~13 11~12 | _ | _ | _ | _ | 730 | 850 | 1,180 | _ | _ | _ |
| PSCKNK | | * 10 | | | M5 | | | | | | | 7 | M5 | 12 | 12 | 730 | 850 | 1,130 | 930 | 1,050 | 1,330 |
| SSCKNK | | 12 | | | | | | | | | | I | _ | _ | _ | 730 | 850 | 1,130 | - | _ | _ |
| | 20 | * 10 | 40 | | | | | | 14 | 7 | 13 | 9 | M5 | 14 | 14 | 880 | 1,020 | 1,250 | 1,080 | 1,120 | 1,450 |
| (側面取付穴タイプ) | | 12 | 40 | 30 | | | | | | | | | | | _ | 920 | 1,070 | 1,520 | _ | _ | _ |
| SCJNK | | 15 | 45 | | M6 | 6.6 | 6 | | 15 | 8 | 13~15 | _ | _ | _ | | 1,000 | 1,100 | 1,570 | _ | _ | _ |
| PSCJNK | 25 | 12 | 40 | 36 | M5 | 5.5 | 4.5 | | 17 | 7 | 16 | | | | | 980 | 1,100 | 1,620 | _ | _ | _ |
| SSCJNK | 20 | * 15 | 50 | 30 | | | | | 18 | 10 | 16~18 18~20 | 10 | M5 | 17 | 16 | 1,050 | 1,130 | 1,800 | 1,150 | 1,200 | 1,820 |
| (カット面取付穴タイプ、 側面取付穴タイプは *印のついたサイズのみ | 30 | * 15 | 55 | 41 | M6 | 6.6 | 6 | | 20 | 10 | | 10 | M6 | 20 | 20 | 1,200 | 1,400 | 2,100 | 1,300 | 1,500 | 2,200 |
| | 35 | 15 | 60 | 46 | | | | 2 | 23 | 12 | 21 | - | _ | _ | _ | 1,250 | 1,520 | 2,770 | _ | _ | _ |
| | 40 | * 18 | 70 | 53 | M8 | 9 | 7 | 2 | 26 | 13 | 23 | 12 | M8 | 26 | 26 | 1,450 | 1,700 | 3,650 | 1,600 | 1,900 | 3,750 |

Ŝカット面取付穴タイプD10の寸法は8になります。

[・]カット面取付穴タイプのD10~16のM1有効ネジ深さは 7mm(下穴貫通)、D20は9mm(下穴貫通)、その他 についてはネジ貫通となっています。